

WebGL Massively Multiplayer Online Game

Student
Gianni Chen
giannic@seas.upenn.edu
University of Pennsylvania

Advisor
Professor Norm Badler
badler@seas.upenn.edu
University of Pennsylvania

Advisor
Aline Normoyle
alinen@seas.upenn.edu
University of Pennsylvania



Figure 1: *Hexmki, HexGL's main model*

Abstract

We will build a multiplayer online game using WebGL and web sockets. Players will connect to a server in their browsers and be able to view other players who are also connected. The goal of each player is to eliminate the others in a free for all format. The players are ranked through the prescribed calculations involving eliminations, deaths, and other properties. This is a simplified combination of current approaches which are either solely WebGL demonstrations or HTML5 and web socket games. One of our primary goals is to provide a stepping stone to build more sophisticated multiplayer online WebGL games.

Project Blog: <http://webglmмо.blogspot.com>

1 Introduction

Since the late 1990s, Massively multiplayer online games (MMOG) have been a popular alternative to other games as well as a pleasant escape from everyday life. This was made possible not only by the improvements to our internet systems, but also by the increased power of our local machines. More recently, many classic games have been making reimagined appearances as MMOGs in our browsers. Common ways to achieve the real-time aspect include Comet, a model which allows pushing of data to a browser without request, and sockets, which has a variety of implementations on the web for asynchronous input and output. We have also seen a movement of 3D graphics towards the web, starting from Flash to Canvas 3D and in 2011, the first stable release of the Web Graphics Library (WebGL). While WebGL allows for both 2D and 3D rendering, the *multiplayer* games we currently see are often in 2D. It is rare to see a multiplayer online game built in 3D using WebGL.

In the initial time frame of this project, we will implement a barebone game. The motivation is not to build the next World

of Warcraft, but to set a base for those who would like to build full-feature multiplayer WebGL games in the future. Though the code base will be presented as a game instead of a boilerplate, parts of it should be adaptable to new environments for their respective purposes. This will be helpful to the games community as well as related researchers because it can be used as a rapid prototyping tool. There are parallels that can be drawn between this project and tools such as Twitter Bootstrap for their base functionalities in different fields.

Our project aims to combine the two very new technologies, WebGL and WebSocket, to build a very simple 3D MMOG. We will start by learning the technologies required for implementation. Once some familiarity is established, we will first implement an interactive 2D environment in WebGL for a local machine. Then, we will build upon that to make a 3D environment, bringing it a step closer to the desired look and feel. At this stage, we will begin to prototype some game features and dynamics. Then, we can begin experimenting with the WebSocket protocol on the 2D prototype to support multiple players. Once we successfully have multiplayer input, we will generalize it to the 3D environment to achieve our desired outcome.

This project makes the following contributions:

- Explores a new alternative for gamers on the web
- Establishes a new front and back end combination for web games and developers who may be interested
- Provides base code for future WebGL multiplayer environments

1.1 Design Goals

There are two major audiences for this project: casual online gamers and web game developers. The target consumer is any person who has access to the web and has an interest in interacting with

others through games. This is a broad audience, but we have seen in the past that many people are fascinated by interactions as simple as seeing people in another continent through a camera in the shape of a telescope on the street (Appendix). We want users to feel a competitive connection with others who are in the same virtual space. On the other end of the spectrum, this framework will target game developers, especially those interested in web technologies. Like Twitter Bootstrap provides website developers a quick way to host content, this project will allow game developers a quick way to build a functional game.

1.2 Project Proposed Features and Functionality

This project implements the following features and functionality:

- An interactive 3D environment accessible by anyone with a WebGL supported browser
- Support for multiple players to interact in the environment
- A way for players to navigate the environment
- A way for players to eliminate one another
 - e.g. weapons, elements etc.
- A competitive way for players to avoid being eliminated
 - e.g. jumping, shielding, etc.
- A presentable and deliverable open source base code

2 Related Work

Web games in the browser collectively have the largest user base. This reason has driven development for this particular medium for games to explode in the past two years. While the traditional tools used to build these were Java and Flash, more and more developers have chosen to move to HTML5 due to its advantages in efficiency and compatibility. More recently, with the release of WebGL, some developers have experimented with it in conjunction with HTML5 for its advanced rendering capabilities. It is difficult to find official papers on this subject in graphics conferences, but there have been some presentations and courses. One such example that I will be using as a tool for learning this technology is *Introduction to WebGL* [Jacob 2012]. Found across the web, we see a variety of projects from individual developers to larger organizations. We have described a few notable ones.

2.1 Khronos Group SIGGRAPH

The Khronos Group consists of media centric companies such as NVIDIA, Electronic Arts, and Google, among others. They focus on creating "open standard, royalty-free APIs" which allow graphics developers to create content for interested users or consumers. At SIGGRAPH, they have a variety of presentations on these standards and libraries, including tutorials which give an overview of their current capabilities. For example, at SIGGRAPH 2012, they presented *Graphics Programming for the Web: WebGL* [Russel and Mo 2012].

2.2 Chrome Experiments

Chrome Experiments, hosted by Google, is a collection of some of the most creative web experiments using cutting edge web technologies such as HTML5 and WebGL. They demonstrate just how powerful these tools are and provide a point of references for state-of-the-art web technologies. Many developers have built their applications with this collection as a driving force for improvement. Many of these submissions have are open source and provide a useful means of learning the standards, conventions, and techniques in developing with these tools. For instance, in the projects tagged multiplayer, DCubic has implemented a space where multiple users can connect and create cubes in space of various colors and animation features [Perez-Fadon 2012].

2.3 BrowserQuest

BrowserQuest is a MMORPG adventure game built by Mozilla Foundation [allergic 2013] and Little Workshop. Little Workshop is a duo, Guillaume Lecollinet and Frank Lecollinet, based in Paris, France [Lecollinet and Lecollinet 2012]. It is implemented using HTML5 Canvas and WebSockets. It is now an open source project hosted on Github. It was originally meant to be a demo of how these technologies can be used to implement a game, explaining why the in-game population has declined since. It hosts several load-balanced servers, with multiple environment in each one. Upon connection, the player can interact with other players in the environment they were connected to. Another notable contribution of BrowserQuest is its compatibility with mobile devices (iOS, Android, Firefox).

2.4 HexGL

HexGL is a HTML5 and WebGL game single player racing game built by Thibaut Despoulain, a senior Computer Engineering student at Université de technologie Belfort-Montbéliard. This too, had optimizations to bring the game to mobile. This impressive demo was one of the first noted to use three.js, a library built on top of WebGL. For that reason, it was later added as an entry to Chrome Experiments [Despoulain 2012].

3 Project Proposal

This project aims to create a functional 3-dimensional Massively Multiplayer Online Game. Its core components will be implemented with WebGL and the WebSockets protocol. We will first build a 3D environment. This will likely be a simple terrain, but is a means for interaction between multiple players. This space will be populated by users connecting from remote locations. Each user may be represented by something as simple as geometry moving in perspective space on keyboard input.

The key here is that the users can interact with each other with minimal delay. To demonstrate this, the game will be a standard deathmatch, where any given player tries to eliminate as many other players as possible in order to climb the rankings. Upon elimination, a player will respawn in a random location.

The means of attack for a player will be via a "shockwave" that radially emanates from the player itself in the horizontal plane. Other players can avoid elimination by jumping, that is changing their vertical height temporarily. This is a simple framework that will set a starting point for more sophisticated renderings of future MMOGs built with the same stack.

3.1 Anticipated Approach

The environment for this game will be in a finite space. We will define the terrain first with a simple rectangle, then import a terrain defined by an object file with changes in elevation at different points. This terrain will be the minimum y value any player can be at. That is, it will be a rigid collision object.

Suppose for now our players are represented by spheres. Each player has 2 possible actions: to attack or jump. To attack, a circle, representing a shockwave, concentric with the player in the horizontal plane will be generated. Over a short period of time, this circle will expand in radius and decay in power until it reaches 0, at which point it will disappear. To jump, the player will follow a simple $f = mg$ update of the player given some initial velocity in the y direction and a constant horizontal velocity at the point of take off [Kankaanpaa 2004]. For any player, if their model intersects with another player's shockwave, their HP will decrease. Once a player's HP falls below 0, they are pronounced eliminated and will respawn after a delay in another location.

This will be implemented by keeping lists of players and shockwaves. At each timestep in the game, each player will be checked against the list of shockwaves for intersections. For each intersection, their HP will fall a predefined constant amount. At the end of each time step, players who died will have their deaths incremented by 1 and players who eliminated others will have their kills incremented by the number of players they eliminated. These statistics will be used to rank players.

The multiplayer portion will be implemented through handling WebSockets using the socket.io API. We will use node.js to host a server to which multiple computers can connect to. Socket.io then allows us to pass data back and forth between the server and each client. This way, when one client has a state change, everyone else will get the same update.

3.2 Target Platforms

I will be using the standard web front-end technologies, HTML, CSS, and Javascript. Building on top of this, I will be using WebGL and related libraries such as three.js. For socket handling, I will be using socket.io. Finally, I will likely be using node.js to host the server. The user will be able to access this online game through any browser and machine that supports WebGL (e.g. Chrome, Firefox, etc.).

3.3 Evaluation Criteria

This MMOG will be evaluated under these criteria:

- Is this method a step forward from traditional methods of creating online games?
- Does the game show that WebGL and WebSockets is a feasible future direction in online gaming?
- How well are players synchronized in the world with the rest of the population?
- Does the game have potential to be adapted and morphed into more sophisticated games?
- How easy is it to get started building a larger game off of this one?

4 Research Timeline

4.1 Project Milestone Report (Alpha Version)

- Complete all background reading
- Experiment with simple prototypes of 2D games combined with WebSockets
- Experiment with 3D WebGL renderings of simple geometry
- Architect the modular pieces of the code and how their contracts with other parts

4.2 Project Final Deliverables

- Fully functional 3D MMOG built in WebGL with WebSockets
- Hosted game so users have access from anywhere on the internet
- Documentation that makes it easy for a user to build off of this game

4.3 Project Future Tasks

- Optimize connections and renderings to scale the application for more connections
- Integrate more physically based calculations into player interactions
 - e.g. pushback from another player's attack
- Assign object models to players to make for a better demonstration
- Apply more sophisticated renderings of animations
 - e.g. particle systems, lights
- Create more detailed terrains so they can be full maps with obstacles

5 Appendix

A list of resources that I used, but did not quite belong in references.

- Multiplayer Chrome Experiments
<http://www.chromeexperiments.com/tag/multiplayer>
- WebSocket Wikipedia
<http://en.wikipedia.org/wiki/WebSocket>
- Comet Applications Wikipedia
[http://en.wikipedia.org/wiki/Comet_\(programming\)](http://en.wikipedia.org/wiki/Comet_(programming))
- Telescope between New York and London
<http://www.cnn.com/2008/WORLD/europe/05/22/scope.project>
- SketchFab
<https://www.sketchfab.com>
- Learning WebGL
<http://learningwebgl.com>

I will fill in the following sections as I make progress on my project, particularly for the alpha review and the final deliverable.

6 Method

7 Results

8 Conclusions

9 Future Work

References

- ALLERGIC, JSWISHER, K. E. A., 2013. Mozilla developer network: WebGL. <https://developer.mozilla.org/en-US/docs/WebGL>.
- DESPOULAIN, T., 2012. Hexgl. <http://hexgl.bkcore.com>.
- I. FETTE, A. M., 2011. Websockets. <http://www.websocket.org/aboutwebsocket.html>, December.
- JACOB, B., 2012. Fitc spotlight javascript: Introduction to webgl. <http://people.mozilla.org/~bjacob/webgl-spotlight-js-2012/>.
- KANKAANPAA, H., 2004. Doing gravity right @ONLINE. <http://www.niksula.hut.fi/hkankaan/Homepages/gravity.html>.
- LECOLLINET, G., AND LECOLLINET, F., 2012. Browserquest. <http://www.littleworkshop.fr/browserquest.html>.
- MARRIN, C., 2011. WebGL specification. <https://www.khronos.org/registry/webgl/specs/1.0/>.
- PEREZ-FADON, D., 2012. Dcubic. <http://www.dcubic.net/html5/>.

RUSSEL, K., AND MO, Z., 2012. Graphics programming for the web: WebGL. ACM SIGGRAPH 2012 Course Slides, August.

VANIK, B., 2012. Acm siggraph presentation: Multiplayer javascript/webgl voxel world game. <https://github.com/benvanik/blk-game>.




Figure 2: Gantt Chart Tentative Schedule