

CIS 500 — Software Foundations
Midterm II

November 8, 2006

Name: _____

Email: _____

Section: _____ 500-001 (Ph.D.)
 _____ 500-002 (MSE / undergraduate)

	Score
1	
2	
3	
4	
5	
6	
7	
8	
Total	

Instructions

- This is a closed-book exam.
- You have 80 minutes to answer all of the questions. The entire exam is worth 80 points for students in section 002 and 90 points for students in section 001 (there is one PhD-section-only problem).
- Questions vary significantly in difficulty, and the point value of a given question is not always exactly proportional to its difficulty. Do not spend too much time on any one question.
- Partial credit will be given. All correct answers are short. The back side of each page and the companion handout may be used as scratch paper.
- Good luck!

References

The following problems concern the simply typed lambda calculus with references. This system is summarized on page 4 of the companion handout.

1. (5 points) Give a well-typed term whose evaluation (beginning in the empty store) will produce the following store when evaluation terminates:

$$\begin{aligned} &(l_1 \mapsto \lambda x:\text{Nat}. (!l_2) \ x, \\ & \ l_2 \mapsto \lambda x:\text{Nat}. (!l_1) \ x) \end{aligned}$$

2. (8 points)

- (a) Give a well-typed term whose evaluation (beginning in the empty store) will produce the following store when evaluation terminates.

$$\begin{aligned} \mu = &(l_1 \mapsto 5, \\ & \ l_2 \mapsto l_1, \\ & \ l_3 \mapsto l_2) \end{aligned}$$

- (b) Give a store typing Σ corresponding to this store (i.e., such that $\emptyset|\Sigma \vdash \mu$).

3. (8 points) Is there a well-typed term whose evaluation (beginning in the empty store) will produce the following store when evaluation terminates?

$$\mu = (l_1 \mapsto l_2, \\ l_2 \mapsto l_3, \\ l_3 \mapsto l_1)$$

If so, give it. If not, explain briefly why no such term exists.

Exceptions

This problem concerns the simply typed lambda calculus with exceptions carrying numeric values—i.e., the system defined in TAPL Section 14.3, where the “exception type” T_{exn} is taken to be $\mathbb{N}at$. This system is summarized on page 1 of the companion handout.

4. (9 points) For each of the following terms, first check whether the term is well typed. If it is, write its type (if the term has multiple types, pick any one of them) and give the final result of evaluating the term (which will be either a value or `raise nv` for some numeric value `nv`). If it is not, write *ill typed*.

(a) `raise (if raise 1 then raise 2 else raise 3)`

(b) `try
 succ (raise 4)
with
 ($\lambda x:\mathbb{N}at.$ true)`

(c) `(try
 ($\lambda x:\mathbb{N}at.$ raise 5)
with
 ($\lambda x:\mathbb{N}at.$ x))
6`

Subtyping

The following problems concern the simply typed lambda calculus with subtyping (and records and variants). This system is summarized on page 7 of the companion handout.

5. (8 points) Draw a derivation tree for the following subtyping statement:

$$\{a:\text{Top}, b:\{\}\rightarrow\{\}, c:\{x:\text{Nat}\}\} <: \{b:\{\}\rightarrow\text{Top}, c:\{\}\}$$

6. (20 points)

Recall the following properties of the simply typed lambda-calculus with subtyping:

- *Progress*: If $\vdash t : T$, then either t is a value or else $t \longrightarrow t'$ for some t' .
- *Preservation*: If $\Gamma \vdash t : T$ and $t \longrightarrow t'$, then $\Gamma \vdash t' : T$.

Each part of this exercise suggests a different way of changing the language. (These changes are not cumulative: each part starts from the original language.) In each part, indicate (by circling TRUE or FALSE) whether each property remains true or becomes false after the suggested change. If a property becomes false, give a counterexample.

(a) Suppose we add the following typing rule:

$$\frac{\Gamma \vdash t : S_1 \rightarrow S_2 \quad S_1 <: S_2 \quad S_2 <: S_1 \quad S_2 <: T_2}{\Gamma \vdash t : T_1 \rightarrow T_2}$$

Progress: TRUE FALSE. For example...

Preservation: TRUE FALSE. For example...

(b) Suppose we add the following evaluation rule:

$$\{\} \longrightarrow (\lambda x : \text{Top}. x)$$

Progress: TRUE FALSE. For example...

Preservation: TRUE FALSE. For example...

(c) Suppose we add the following subtyping rule:

$$\langle \rangle <: \{\}$$

Progress: TRUE FALSE. For example...

Preservation: TRUE FALSE. For example...

(d) Suppose we add the following subtyping rule:

$$\{\} <: \langle \rangle$$

Progress: TRUE FALSE. For example...

Preservation: TRUE FALSE. For example...

7. (22 points) Fill in the missing steps in the proof of the subtyping inversion lemma for arrow types from Chapter 15. Your wording does not need to exactly match what is in the book or lecture notes, but every step required in the proof (use of an assumption, use of the induction hypothesis, or use of a subtyping rule) must be mentioned explicitly.

Lemma: If $S <: T_1 \rightarrow T_2$, then S has the form $S_1 \rightarrow S_2$, with $T_1 <: S_1$ and $S_2 <: T_2$.

Proof: By induction on subtyping derivations. By inspection of the subtyping rules, it is clear that the final rule in the derivation of $S <: T_1 \rightarrow T_2$ must be S-REFL, S-TRANS, or S-ARROW.

Case S-REFL: $S = T_1 \rightarrow T_2$

Case S-TRANS: $S <: U$ $U <: T_1 \rightarrow T_2$

Case S-ARROW: $S = S_1 \rightarrow S_2$ $T_1 <: S_1$ $S_2 <: T_2$

8. (10 points) **(For students in the PhD section only.)**

Section 15.5 in the book discusses two ways of combining subtyping with references. The first uses just the **Ref** type constructor, with a simple subtyping rule:

$$\frac{S_1 <: T_1 \quad T_1 <: S_1}{\text{Ref } S_1 <: \text{Ref } T_1} \quad (\text{S-REF})$$

The second, more refined, treatment introduces two new type constructors, **Source** and **Sink**—intuitively, **Source** T is thought of as a capability to read values of type T from a cell (but which does not permit assignment), while **Sink** T is a capability to write to a cell. **Ref** T is intuitively a combination of these two capabilities, giving permission both to read and to write.

The typing rule for reference creation returns a **Ref** (it is unchanged from Chapter 13), while the rules for dereferencing and assignment are changed to demand only the appropriate capability. The details of these rules are not important for this question, but they are reproduced, for reference, on 9 of the companion handout.

The subtyping relation is extended with a rules stating that the **Source** constructor is contravariant, the **Sink** constructor is covariant, and the **Ref** constructor can be promoted to either **Source** or **Sink**.

$$\frac{S_1 <: T_1}{\text{Source } S_1 <: \text{Source } T_1} \quad (\text{S-SOURCE})$$

$$\frac{T_1 <: S_1}{\text{Sink } S_1 <: \text{Sink } T_1} \quad (\text{S-SINK})$$

$$\text{Ref } T_1 <: \text{Source } T_1 \quad (\text{S-REFSOURCE})$$

$$\text{Ref } T_1 <: \text{Sink } T_1 \quad (\text{S-REFSINK})$$

If we know that $S <: T$ and we know something about the shape of T , the subtype inversion lemma gives us information about the shape of S and the subtype relationships that must hold between the sub-expressions of S and T . For example, question 7 above asked you to prove the arrow case.

Fill in appropriate statements for the cases of the subtyping inversion lemma for the constructors **Ref**, **Source**, and **Sink**. You do not need to give proofs.

(a) If $S <: \text{Ref } T_1$, then

(b) If $S <: \text{Source } T_1$, then

(c) If $S <: \text{Sink } T_1$, then

Companion handout

Full definitions of the systems
used in the exam

Simply-typed lambda calculus with error handling (and numbers and booleans), using Nat as the T_{exn} type

Syntax

$t ::=$
 true
 false
 if t then t else t
 0
 succ t
 pred t
 iszero t
 x
 $\lambda x:T.t$
 $t t$
 raise t
 try t with t

$v ::=$
 true
 false
 nv
 $\lambda x:T.t$

$nv ::=$
 0
 succ nv

$T ::=$
 Bool
 Nat
 $T \rightarrow T$

$\Gamma ::=$
 \emptyset

Evaluation

terms

constant true
 constant false
 conditional
 constant zero
 successor
 predecessor
 zero test
 variable
 abstraction
 application
 raise exception
 handle exceptions

values

true value
 false value
 numeric value
 abstraction value

numeric values

zero value
 successor value

types

type of booleans
 type of natural numbers
 type of functions

type environments

empty type env.

$t \longrightarrow t'$

if true then t_2 else $t_3 \longrightarrow t_2$ (E-IFTRUE)

if false then t_2 else $t_3 \longrightarrow t_3$ (E-IFFALSE)

$$\frac{t_1 \longrightarrow t'_1}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \longrightarrow \text{if } t'_1 \text{ then } t_2 \text{ else } t_3} \quad \text{(E-IF)}$$

$$\frac{t_1 \longrightarrow t'_1}{\text{succ } t_1 \longrightarrow \text{succ } t'_1} \quad \text{(E-SUCC)}$$

pred 0 \longrightarrow 0 (E-PREDZERO)

pred (succ nv_1) \longrightarrow nv_1 (E-PREDSUCC)

$$\begin{array}{c}
\frac{t_1 \longrightarrow t'_1}{\text{pred } t_1 \longrightarrow \text{pred } t'_1} \quad (\text{E-PRED}) \\
\text{iszero } 0 \longrightarrow \text{true} \quad (\text{E-ISZEROZERO}) \\
\text{iszero } (\text{succ } nv_1) \longrightarrow \text{false} \quad (\text{E-ISZEROSUCC}) \\
\frac{t_1 \longrightarrow t'_1}{\text{iszero } t_1 \longrightarrow \text{iszero } t'_1} \quad (\text{E-ISZERO}) \\
\frac{t_1 \longrightarrow t'_1}{t_1 \ t_2 \longrightarrow t'_1 \ t_2} \quad (\text{E-APP1}) \\
\frac{t_2 \longrightarrow t'_2}{v_1 \ t_2 \longrightarrow v_1 \ t'_2} \quad (\text{E-APP2}) \\
(\lambda x:T_{11}.t_{12}) \ v_2 \longrightarrow [x \mapsto v_2]t_{12} \quad (\text{E-APPABS}) \\
(\text{raise } v_{11}) \ t_2 \longrightarrow \text{raise } v_{11} \quad (\text{E-APPRAISE1}) \\
v_1 \ (\text{raise } v_{21}) \longrightarrow \text{raise } v_{21} \quad (\text{E-APPRAISE2}) \\
\frac{t_1 \longrightarrow t'_1}{\text{raise } t_1 \longrightarrow \text{raise } t'_1} \quad (\text{E-RAISE}) \\
\text{raise } (\text{raise } v_{11}) \longrightarrow \text{raise } v_{11} \quad (\text{E-RAISERAISE}) \\
\text{if raise } v_{11} \text{ then } t_2 \text{ else } t_3 \longrightarrow \text{raise } v_{11} \quad (\text{E-IFRAISE}) \\
\text{try } v_1 \text{ with } t_2 \longrightarrow v_1 \quad (\text{E-TRYV}) \\
\text{try raise } v_{11} \text{ with } t_2 \longrightarrow t_2 \ v_{11} \quad (\text{E-TRYRAISE}) \\
\frac{t_1 \longrightarrow t'_1}{\text{try } t_1 \text{ with } t_2 \longrightarrow \text{try } t'_1 \text{ with } t_2} \quad (\text{E-TRY})
\end{array}$$

Typing

$$\begin{array}{c}
\boxed{\Gamma \vdash t : T} \\
\Gamma \vdash \text{true} : \text{Bool} \quad (\text{T-TRUE}) \\
\Gamma \vdash \text{false} : \text{Bool} \quad (\text{T-FALSE}) \\
\frac{\Gamma \vdash t_1 : \text{Bool} \quad \Gamma \vdash t_2 : T \quad \Gamma \vdash t_3 : T}{\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF}) \\
\Gamma \vdash 0 : \text{Nat} \quad (\text{T-ZERO}) \\
\frac{\Gamma \vdash t_1 : \text{Nat}}{\Gamma \vdash \text{succ } t_1 : \text{Nat}} \quad (\text{T-SUCC})
\end{array}$$

$$\frac{\Gamma \vdash t_1 : \text{Nat}}{\Gamma \vdash \text{pred } t_1 : \text{Nat}} \quad (\text{T-PRED})$$

$$\frac{\Gamma \vdash t_1 : \text{Nat}}{\Gamma \vdash \text{iszero } t_1 : \text{Bool}} \quad (\text{T-ISZERO})$$

$$\frac{x:T \in \Gamma}{\Gamma \vdash x : T} \quad (\text{T-VAR})$$

$$\frac{\Gamma, x:T_1 \vdash t_2 : T_2}{\Gamma \vdash \lambda x:T_1. t_2 : T_1 \rightarrow T_2} \quad (\text{T-ABS})$$

$$\frac{\Gamma \vdash t_1 : T_{11} \rightarrow T_{12} \quad \Gamma \vdash t_2 : T_{11}}{\Gamma \vdash t_1 \ t_2 : T_{12}} \quad (\text{T-APP})$$

$$\frac{\Gamma \vdash t_1 : \text{Nat}}{\Gamma \vdash \text{raise } t_1 : T} \quad (\text{T-EXN})$$

$$\frac{\Gamma \vdash t_1 : T \quad \Gamma \vdash t_2 : \text{Nat} \rightarrow T}{\Gamma \vdash \text{try } t_1 \text{ with } t_2 : T} \quad (\text{T-TRY})$$

Simply-typed lambda calculus with references (and Unit, Nat, Bool)

Syntax

$t ::=$
 unit
 x
 $\lambda x:T.t$
 $t t$
 ref t
 $!t$
 $t := t$
 l
 true
 false
 if t then t else t
 0
 succ t
 pred t
 iszero t

$v ::=$
 unit
 $\lambda x:T.t$
 l
 true
 false
 nv

$T ::=$
 Unit
 $T \rightarrow T$
 Ref T
 Bool
 Nat

$\mu ::=$
 \emptyset
 $\mu, l = v$

$\Gamma ::=$
 \emptyset
 $\Gamma, x:T$

$\Sigma ::=$
 \emptyset
 $\Sigma, l:T$

$nv ::=$
 0
 succ nv

terms

constant unit
 variable
 abstraction
 application
 reference creation
 dereference
 assignment
 store location
 constant true
 constant false
 conditional
 constant zero
 successor
 predecessor
 zero test

values

constant **unit**
 abstraction value
 store location
 true value
 false value
 numeric value

types

unit type
 type of functions
 type of reference cells
 type of booleans
 type of natural numbers

stores

empty store
 location binding

type environments

empty type env.
 term variable binding

store typings

empty store typing
 location typing

numeric values

zero value
 successor value

$$\boxed{t|\mu \longrightarrow t'|\mu'}$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{t_1 \ t_2|\mu \longrightarrow t'_1 \ t_2|\mu'} \quad (\text{E-APP1})$$

$$\frac{t_2|\mu \longrightarrow t'_2|\mu'}{v_1 \ t_2|\mu \longrightarrow v_1 \ t'_2|\mu'} \quad (\text{E-APP2})$$

$$(\lambda x:T_{11}.t_{12}) \ v_2|\mu \longrightarrow [x \mapsto v_2]t_{12}|\mu \quad (\text{E-APPABS})$$

$$\frac{l \notin \text{dom}(\mu)}{\text{ref } v_1|\mu \longrightarrow l|(\mu, l \mapsto v_1)} \quad (\text{E-REFV})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{\text{ref } t_1|\mu \longrightarrow \text{ref } t'_1|\mu'} \quad (\text{E-REF})$$

$$\frac{\mu(l) = v}{!l|\mu \longrightarrow v|\mu} \quad (\text{E-DEREFLOC})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{!t_1|\mu \longrightarrow !t'_1|\mu'} \quad (\text{E-DEREF})$$

$$l := v_2|\mu \longrightarrow \text{unit}[l \mapsto v_2]|\mu \quad (\text{E-ASSIGN})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{t_1 := t_2|\mu \longrightarrow t'_1 := t_2|\mu'} \quad (\text{E-ASSIGN1})$$

$$\frac{t_2|\mu \longrightarrow t'_2|\mu'}{v_1 := t_2|\mu \longrightarrow v_1 := t'_2|\mu'} \quad (\text{E-ASSIGN2})$$

$$\text{if true then } t_2 \text{ else } t_3|\mu \longrightarrow t_2|\mu \quad (\text{E-IFTRUE})$$

$$\text{if false then } t_2 \text{ else } t_3|\mu \longrightarrow t_3|\mu \quad (\text{E-IFFALSE})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3|\mu \longrightarrow \text{if } t'_1 \text{ then } t_2 \text{ else } t_3|\mu'} \quad (\text{E-IF})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{\text{succ } t_1|\mu \longrightarrow \text{succ } t'_1|\mu'} \quad (\text{E-SUCC})$$

$$\text{pred } 0|\mu \longrightarrow 0|\mu \quad (\text{E-PREDZERO})$$

$$\text{pred } (\text{succ } nv_1)|\mu \longrightarrow nv_1|\mu \quad (\text{E-PREDSUCC})$$

$$\frac{t_1|\mu \longrightarrow t'_1|\mu'}{\text{pred } t_1|\mu \longrightarrow \text{pred } t'_1|\mu'} \quad (\text{E-PRED})$$

$$\text{iszero } 0|\mu \longrightarrow \text{true}|\mu \quad (\text{E-ISZEROZERO})$$

$\text{iszero } (\text{succ } \text{nv}_1)|\mu \longrightarrow \text{false}|\mu$ (E-ISZEROSUCC)

$$\frac{\text{t}_1|\mu \longrightarrow \text{t}'_1|\mu'}{\text{iszero } \text{t}_1|\mu \longrightarrow \text{iszero } \text{t}'_1|\mu'} \quad (\text{E-ISZERO})$$

Typing

$\boxed{\Gamma|\Sigma \vdash \text{t} : \text{T}}$

$\Gamma|\Sigma \vdash \text{unit} : \text{Unit}$ (T-UNIT)

$$\frac{\text{x}:\text{T} \in \Gamma}{\Gamma|\Sigma \vdash \text{x} : \text{T}} \quad (\text{T-VAR})$$

$$\frac{\Gamma, \text{x}:\text{T}_1|\Sigma \vdash \text{t}_2 : \text{T}_2}{\Gamma|\Sigma \vdash \lambda \text{x}:\text{T}_1. \text{t}_2 : \text{T}_1 \rightarrow \text{T}_2} \quad (\text{T-ABS})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{T}_{11} \rightarrow \text{T}_{12} \quad \Gamma|\Sigma \vdash \text{t}_2 : \text{T}_{11}}{\Gamma|\Sigma \vdash \text{t}_1 \text{ t}_2 : \text{T}_{12}} \quad (\text{T-APP})$$

$$\frac{\Sigma(l) = \text{T}_1}{\Gamma|\Sigma \vdash l : \text{Ref } \text{T}_1} \quad (\text{T-LOC})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{T}_1}{\Gamma|\Sigma \vdash \text{ref } \text{t}_1 : \text{Ref } \text{T}_1} \quad (\text{T-REF})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Ref } \text{T}_{11}}{\Gamma|\Sigma \vdash !\text{t}_1 : \text{T}_{11}} \quad (\text{T-DEREF})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Ref } \text{T}_{11} \quad \Gamma|\Sigma \vdash \text{t}_2 : \text{T}_{11}}{\Gamma|\Sigma \vdash \text{t}_1 := \text{t}_2 : \text{Unit}} \quad (\text{T-ASSIGN})$$

$\Gamma|\Sigma \vdash \text{true} : \text{Bool}$ (T-TRUE)

$\Gamma|\Sigma \vdash \text{false} : \text{Bool}$ (T-FALSE)

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Bool} \quad \Gamma|\Sigma \vdash \text{t}_2 : \text{T} \quad \Gamma|\Sigma \vdash \text{t}_3 : \text{T}}{\Gamma|\Sigma \vdash \text{if } \text{t}_1 \text{ then } \text{t}_2 \text{ else } \text{t}_3 : \text{T}} \quad (\text{T-IF})$$

$\Gamma|\Sigma \vdash 0 : \text{Nat}$ (T-ZERO)

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Nat}}{\Gamma|\Sigma \vdash \text{succ } \text{t}_1 : \text{Nat}} \quad (\text{T-SUCC})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Nat}}{\Gamma|\Sigma \vdash \text{pred } \text{t}_1 : \text{Nat}} \quad (\text{T-PRED})$$

$$\frac{\Gamma|\Sigma \vdash \text{t}_1 : \text{Nat}}{\Gamma|\Sigma \vdash \text{iszero } \text{t}_1 : \text{Bool}} \quad (\text{T-ISZERO})$$

Simply-typed lambda calculus with subtyping (and records and variants)

Syntax

$t ::=$
 x
 $\lambda x:T. t$
 $t t$
 $\{l_i=t_i \ i \in 1..n\}$
 $t.l$
 $\langle l=t \rangle$ (no as)
 $\text{case } t \text{ of } \langle l_i=x_i \rangle \Rightarrow t_i \ i \in 1..n$

$v ::=$
 $\lambda x:T. t$
 $\{l_i=v_i \ i \in 1..n\}$

$T ::=$
 $\{l_j:T_i \ i \in 1..n\}$
 Top
 $T \rightarrow T$
 $\langle l_i:T_i \ i \in 1..n \rangle$

$\Gamma ::=$
 \emptyset

terms

variable
abstraction
application
record
projection
tagging
case

values

abstraction value
record value

types

type of records
maximum type
type of functions
type of variants

type environments
empty type env.

Evaluation

$t \longrightarrow t'$

$$\frac{t_1 \longrightarrow t'_1}{t_1 t_2 \longrightarrow t'_1 t_2} \quad (\text{E-APP1})$$

$$\frac{t_2 \longrightarrow t'_2}{v_1 t_2 \longrightarrow v_1 t'_2} \quad (\text{E-APP2})$$

$$(\lambda x:T_{11}. t_{12}) v_2 \longrightarrow [x \mapsto v_2] t_{12} \quad (\text{E-APPABS})$$

$$\{l_i=v_i \ i \in 1..n\}. l_j \longrightarrow v_j \quad (\text{E-PROJRCD})$$

$$\text{case } (\langle l_j=v_j \rangle \text{ as } T) \text{ of } \langle l_i=x_i \rangle \Rightarrow t_i \ i \in 1..n \longrightarrow [x_j \mapsto v_j] t_j \quad (\text{E-CASEVARIANT})$$

$$\frac{t_0 \longrightarrow t'_0}{\text{case } t_0 \text{ of } \langle l_i=x_i \rangle \Rightarrow t_i \ i \in 1..n \longrightarrow \text{case } t'_0 \text{ of } \langle l_i=x_i \rangle \Rightarrow t_i \ i \in 1..n} \quad (\text{E-CASE})$$

$$\frac{t_i \longrightarrow t'_i}{\langle l_i=t_i \rangle \text{ as } T \longrightarrow \langle l_i=t'_i \rangle \text{ as } T} \quad (\text{E-VARIANT})$$

Typing

$\Gamma \vdash t : T$

$$\frac{\text{for each } i \quad \Gamma \vdash t_i : T_i}{\Gamma \vdash \{l_i=t_i \ i \in 1..n\} : \{l_i:T_i \ i \in 1..n\}} \quad (\text{T-RCD})$$

$$\frac{\Gamma \vdash \mathbf{t}_1 : \{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n}\}}{\Gamma \vdash \mathbf{t}_1.l_j : \mathbf{T}_j} \quad (\text{T-PROJ})$$

$$\frac{\mathbf{x} : \mathbf{T} \in \Gamma}{\Gamma \vdash \mathbf{x} : \mathbf{T}} \quad (\text{T-VAR})$$

$$\frac{\Gamma, \mathbf{x} : \mathbf{T}_1 \vdash \mathbf{t}_2 : \mathbf{T}_2}{\Gamma \vdash \lambda \mathbf{x} : \mathbf{T}_1. \mathbf{t}_2 : \mathbf{T}_1 \rightarrow \mathbf{T}_2} \quad (\text{T-ABS})$$

$$\frac{\Gamma \vdash \mathbf{t}_1 : \mathbf{T}_{11} \rightarrow \mathbf{T}_{12} \quad \Gamma \vdash \mathbf{t}_2 : \mathbf{T}_{11}}{\Gamma \vdash \mathbf{t}_1 \ \mathbf{t}_2 : \mathbf{T}_{12}} \quad (\text{T-APP})$$

$$\frac{\Gamma \vdash \mathbf{t} : \mathbf{S} \quad \mathbf{S} <: \mathbf{T}}{\Gamma \vdash \mathbf{t} : \mathbf{T}} \quad (\text{T-SUB})$$

$$\frac{\Gamma \vdash \mathbf{t}_1 : \mathbf{T}_1}{\Gamma \vdash \langle \mathbf{l}_1 = \mathbf{t}_1 \rangle : \langle \mathbf{l}_1 : \mathbf{T}_1 \rangle} \quad (\text{T-VARIANT})$$

$$\frac{\Gamma \vdash \mathbf{t}_0 : \langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n} \rangle \quad \text{for each } i \quad \Gamma, \mathbf{x}_i : \mathbf{T}_i \vdash \mathbf{t}_i : \mathbf{T}}{\Gamma \vdash \text{case } \mathbf{t}_0 \text{ of } \langle \mathbf{l}_i = \mathbf{x}_i \rangle \Rightarrow \mathbf{t}_i^{i \in 1..n} : \mathbf{T}} \quad (\text{T-CASE})$$

Subtyping

$$\boxed{\mathbf{S} <: \mathbf{T}}$$

$$\mathbf{S} <: \mathbf{S} \quad (\text{S-REFL})$$

$$\frac{\mathbf{S} <: \mathbf{U} \quad \mathbf{U} <: \mathbf{T}}{\mathbf{S} <: \mathbf{T}} \quad (\text{S-TRANS})$$

$$\mathbf{S} <: \text{Top} \quad (\text{S-TOP})$$

$$\frac{\mathbf{T}_1 <: \mathbf{S}_1 \quad \mathbf{S}_2 <: \mathbf{T}_2}{\mathbf{S}_1 \rightarrow \mathbf{S}_2 <: \mathbf{T}_1 \rightarrow \mathbf{T}_2} \quad (\text{S-ARROW})$$

$$\{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n+k}\} <: \{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n}\} \quad (\text{S-RCDWIDTH})$$

$$\frac{\text{for each } i \quad \mathbf{S}_i <: \mathbf{T}_i}{\{\mathbf{l}_i : \mathbf{S}_i^{i \in 1..n}\} <: \{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n}\}} \quad (\text{S-RCDDEPTH})$$

$$\frac{\{\mathbf{k}_j : \mathbf{S}_j^{j \in 1..n}\} \text{ is a permutation of } \{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n}\}}{\{\mathbf{k}_j : \mathbf{S}_j^{j \in 1..n}\} <: \{\mathbf{l}_i : \mathbf{T}_i^{i \in 1..n}\}} \quad (\text{S-RCDPERM})$$

$$\langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n} \rangle <: \langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n+k} \rangle \quad (\text{S-VARIANTWIDTH})$$

$$\frac{\text{for each } i \quad \mathbf{S}_i <: \mathbf{T}_i}{\langle \mathbf{l}_i : \mathbf{S}_i^{i \in 1..n} \rangle <: \langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n} \rangle} \quad (\text{S-VARIANTDEPTH})$$

$$\frac{\langle \mathbf{k}_j : \mathbf{S}_j^{j \in 1..n} \rangle \text{ is a permutation of } \langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n} \rangle}{\langle \mathbf{k}_j : \mathbf{S}_j^{j \in 1..n} \rangle <: \langle \mathbf{l}_i : \mathbf{T}_i^{i \in 1..n} \rangle} \quad (\text{S-VARIANTPERM})$$

Typing rules for Source, Sink, and Ref constructors

$$\frac{\Gamma|\Sigma \vdash t_1 : T_1}{\Gamma|\Sigma \vdash \text{ref } t_1 : \text{Ref } T_1} \quad (\text{T-REF})$$

$$\frac{\Gamma|\Sigma \vdash t_1 : \text{Source } T_{11}}{\Gamma|\Sigma \vdash !t_1 : T_{11}} \quad (\text{T-DEREF})$$

$$\frac{\Gamma|\Sigma \vdash t_1 : \text{Sink } T_{11} \quad \Gamma|\Sigma \vdash t_2 : T_{11}}{\Gamma|\Sigma \vdash t_1 := t_2 : \text{Unit}} \quad (\text{T-ASSIGN})$$