

# *A Design for Type-Directed Programming in Java*

Stephanie Weirich  
University of Pennsylvania  
joint work with Liang Huang

# Type-directed programming?

- Defining operations that can be used for many types of data
- Behavior of operation depends on the type of the data
- Third form of polymorphism
  - Subtype polymorphism (Java)
  - Parametric polymorphism (GJ, ML)
  - Ad-hoc polymorphism (TDP)
- Poster child: Serialization

## **Java provides TDP**

---

- Analyze names of types
  - instanceof, cast
- Analyze structure of types
  - Reflection API
  - Discover and access the fields and methods of classes
- Both are important

# Serialization

```
public String serialize(Object obj) {  
    if (obj == null) return "null";  
    if (obj instanceof Integer) {  
        return Integer.toString(  
            ((Integer)obj).intValue());  
    } else if (obj instanceof Boolean) {  
        if ((Boolean)obj) { return "true"; }  
        else { return "false"; }  
    } else if (obj instanceof Float) { ...  
    } else { ...
```

## Serialization (continued)

```
try {
    Class objClass = obj.getClass();
    String result = "[" + objClass + " ";
    Field[] f = objClass.getDeclaredFields();
    for (int i = 0; i < f.length; i++) {
        f[i].setAccessible(true);
        result += f[i].getName() + "=";
        result += serialize( f[i].get( obj ) );
        if (i < (f.length - 1)) result += ",";
    }
    return result += "]";
} catch (IllegalAccessException e) { return "Impossible"; }
}
```

## TDP is not OOP

- Instructors for OO-langs often tell students to replace:

```
if (x instanceof C1) { dosomething1(); }
else if (x instanceof C2) { dosomething2(); }
else if (x instanceof C3) { dosomething3(); }
```

with

```
x.dosomething();
```

and put the functionality in C1,C2,C3.

## **Why not in this case?**

- Serialization is used by *many* classes
- *Each* class needs a method called `serialize`. Implementation dispersed throughout the program.
  - Annoying because there is a general way to define that method.
  - Difficult to change. What if extra state is necessary?
  - May not have access to all classes.

## More examples of TDP

- Operations on data structures:
  - Structural equality, cloning, iterators, visitor pattern
- Proxies/Adaptors
  - Add new functionality to an interface
  - Examples: logging, tracing, profiling
- Dynamic objects
  - Checking interface of dynamically loaded code/data
- JavaBeans
  - Presenting components to users
- Runtime debugging tools

# **Problems with instanceof and Java Reflection**

- Weak guarantees of correctness
  - Almost always requires run-time type casting
- Doesn't integrate well with generics
  - Type parameters are erased in GJ
- Breaks abstraction
  - Can find out “real” type of an object
  - Can access public and private fields of methods

## Our proposal

- Analyze first-class type parameters

```
<T>void m (T x) {  
    // To learn about the type of x  
    // analyze the type parameter T  
}
```

- New operators for discovering the **name** and **structure** of run-time type information.
- Another argument for adding generics to Java.

## **Run-time type information**

---

- Type information provided at run-time to parameterized classes and methods
- NextGen, PolyJ but not GJ, Java 1.5
- More expressive: new T(), (T)
- Downside: Not as compatible with existing code

# **Nominal analysis of type params**

## Nominal analysis of type params

```
<T>void m (T x) {  
    typematch T {  
        case Integer: ...  
        case Boolean: ...  
        case C: ...  
        case List<U>: ...  
        default: ...  
    }  
}
```

## **Comparison with instanceof**

---

- How does typematch compare to instanceof in terms of
  - Eliminating type casts
  - Generics
  - Abstraction

## Nominal analysis of type params

```
<T>void m (T x) {  
    typematch T {  
        case Integer: ... x.intValue() ...  
        case Boolean: ... if (x) then ...  
        case C: ... x.m() ...  
        default: ... can't do anything special with x  
    }  
}
```

No casting needed!  
Change the type of x in  
the branch

## Eliminating casts

- Could we change instanceof to add refinement?

```
Object x;  
if (x instanceof Integer) {  
    ... x.intValue() + 1 ...  
}
```

## Not a sound change

```
class C {  
    Object f = new Integer(3);  
}
```

```
C x;  
if (x.f instanceof Integer) {  
    g();  
    ... x.f.intValue() ...  
}
```

```
void g() {  
    x.f = new Boolean(false);  
}
```

## With typematch

```
class C<T> {  
    T f = null; // Initialize in constructor  
}  
...  
C<T> x;  
typematch T {  
    case Integer:  
        g();  
        ... x.f.intValue() ...  
}
```

g() cannot assign to  
x.f unless it  
determines the  
identity of T

# Typematch eliminates many casts

- Can refine the type of many objects

```
T[] arr;
```

```
typematch T {  
    case Integer:  
        // Know all elements of arr are Integers
```

```
}
```

- With instanceof, must cast each element individually.

## Generics with typematch

- Pattern matching for parameterized classes.

```
typematch T {  
    case List<Integer>:  
        // only matches lists of Integers  
    case List<U>:  
        // matches any list  
}
```

# Generics with instanceof

```
Object x;  
if (x instanceof ???) {  
    ...  
}
```

- GJ: only match general lists.
  - `List<Integer>` is the “same” type as `List` at run time.
  - Can’t distinguish `List<Integer>` from `List<Boolean>`
- NextGen: only match specific instances.
  - `List<Object>` is not a supertype of `List<Integer>`.

# No abstraction with instanceof

- Subtyping is not an abstraction mechanism.

```
class D extends C { ... }
public void m(C x) {
    if (x instanceof D) {
        ...
    }
}
```

- m's caller cannot hide the fact that obj is actually a D

```
D obj = ...;
m(obj);
```

## Abstraction w/ typematch

- Even with parameter analysis, still some information hiding.

```
class D extends C { ... }
public <T extends C>void m(T x) {
    typematch T {
        case D: ...
    }
```

- m's caller can hide the type by changing the type parameter.

```
D obj = ...
m<C>(obj);
```

# Structural Analysis

- Replacement for Java Reflection
- Use pattern matching to iterate over fields and methods of objects.

```
T obj;  
forfield (U f in T) {  
    U field = obj.f;  
    ....  
}
```

- Same issues arise as with typematch

# **Structural analysis**

---

## **Structural analysis**

---

- Additional operations to determine type information
  - `getName<T>`
  - `getNumFields<T>`
  - `getNumMethods<T>`
  - `getFieldName<T,f>`
  - `getMethodName<T,m>`
- Easy but still important.

# Type-Directed Serialization

```
public <T>String pickle ( T obj ) {  
    if (obj == null) return "null";  
    typematch T {  
        case Integer:  
            return Integer.toString(obj.intValue());  
        case Boolean:  
            return Boolean.toString(obj.boolValue());  
        default:  
            String result = "[" + getName<T> + " ";  
            forfield (U f in T) {  
                result += getFieldName<T,f> + "=" + pickle<U>( obj.f );  
            }  
            return result + "]";  
    }  
}
```

# **Pattern matching is natural**

- Can iterate over all integer-valued fields.

```
for field(Integer f in T) {  
    sum += obj.f.intValue();  
}
```

- Can iterate over all void methods.

```
formethod (void m() in T) {  
    if (getMethodName<T,m> == "test") {  
        obj.m();  
    }  
}
```

## Limitation to method iteration

- Can't write a single method pattern to match any method
  - `formethod ( U0 m() in T ) { ... }`
  - `formethod ( U0 m(U1) in T ) { ... }`
  - `formethod ( U0 m(U1,U2) in T ) { ... }`
- Also must specify type parameters
  - `formethod ( X <X>m(X, U) in T ) { ... }`

# **Formal Language**

---

# Formal Language

- We have formalized these ideas in a small language (called TDJ).
  - Explicitly states how type checking works.
  - Necessary to show type soundness.
- TDJ is based on FGJ but has a type-passing semantics.

## TDJ Syntax

- New expression forms, compatible with functional core OO language.
- $e ::= \dots$ 
  - | typematch  $T$  with  $\bar{U}:\bar{e}$  default  $:e'$
  - | fieldfold<sub>i</sub> (  $x = e; T f_x$  in  $U$ )  $e'$
  - | methfold<sub>i</sub> (  $x = e; MT m_x$  in  $T$ )  $e'$
  - |  $e.f_x$  |  $e.m_x$

## New assumptions in context

- Typing context contains new forms of assumptions:  
 $\Delta ::= \text{empty} \mid X <: T$   
     $\mid \Delta, T \ll: U$   
     $\mid \Delta, T \ll: \{ U f_x \}$   
     $\mid \Delta, T \ll: \{ MT m_x \}$
- Used when determining subtyping, checking field/method access.

$\text{matches}(N, T) = \Sigma$  when  $\vdash N <: \Sigma(T)$

## Execution of type match

---

$\text{matches}(N, T) = \Sigma$

---

$\text{typematch } N \text{ with } T : e \cup \bar{e} \text{ default: } e' \mapsto \Sigma(e)$

---

$\text{matches}(N, T)$  not defined

---

$\text{typematch } N \text{ with } T : e \cup \bar{e} \text{ default: } e' \mapsto \text{typematch}$   
 $\bar{e} \text{ default: } e'$

---

$\text{typematch } N \text{ with default: } e' \mapsto e'$

## Type checking typematch

- Add assumptions to context when checking branches

$$\Delta \vdash T, U \text{ ok} \quad \Delta_i \vdash U_i \text{ minok}$$
$$\Delta, \Delta_i, T \ll: U_i ; \Gamma \vdash e_i \in V_i <: U$$

---

$$\Delta; \Gamma \vdash \text{typematch } T \text{ with } \bar{U}; \bar{e} \text{ default: } e' \in U$$

# Can add unsatisfiable assumptions to context

- Occurs when checking dead code.

```
typematch Integer {  
    case Boolean:  
        // who cares whether this branch typechecks?  
}
```

- Smart compiler could omit checking branch.

## Typechecking fieldfold

- Similar to typematch

$$i > 0 \quad \Delta; \Gamma \vdash e : U' \in : U$$
$$\Delta \vdash T' \text{ ok} \quad \Delta' \vdash T \text{ minok}$$
$$\Delta, \Delta', T' \ll: \{T f_x\}; \Gamma, x:U \vdash e' \in U' \in : U$$

---

$$\Delta; \Gamma \vdash \text{fieldfold}_i (x = e; T f_x \text{ in } T') e' \in U$$

## Related work

---

- Lots of related work on run-time type analysis.
- Closest to intensional type analysis
- Adding assumptions to context like GADTs

## Comparison with ITA

- Both systems: type system must propagate discovered type information
  - typecase: type equalities mean that substitution is sufficient.
  - Here: constraints required to propagate information about subtyping.
- Discovering type equalities is more expressive

# Typecase/typematch

- Basing typematch on subtyping limits expressiveness
- With typecase the result type of a branch can depend on the pattern

```
(typecase a of
    int => 0
    bool => false) : a
```

- Unsound for typematch

```
typematch T {
    case Integer: 0 // assume T <: Integer, not =
    case C: new C();
} : T
```

## Future work

---

- Cases for typematch that require the exact type:

```
typematch D {  
    case = C:  
        // even if D <: C this would not fire  
    case sub C:  
        // instead this branch is taken  
}
```

## Future Work

- Currently working on an implementation
  - Using Polyglot to extend PolyJ implementation from Cornell University
- Will help us weigh trade off between abstraction and expressiveness
  - How to deal with public/private/protected for fields and methods?
  - Allow access to the run-time type of an object as a first-class type parameter?

# **Technical Report**

---

- Formalization of typematch and field/method iteration in a core calculus
  - Typing rules and operational semantics for small, FGJ-like language.
- Proof of type soundness.
- More detailed description of related work

# Conclusion

---

- Analyzing type parameters is a more principled approach to type-directed programming than instanceof or Java Reflection.

